

NEW

EBERLE

TS+

The new thermal actuator



HEATING TECHNOLOGY



Characteristics

- Compact and stylish design
- Unique manual position
- Protection type IP 54 in all orientations
- Display of operation status and stroke position (in window at top of cap)
- Can be mounted in any orientation
- Standard M30 x 1.5 mm fitting, no adapter required
- 230 V and 24 V versions
- Low power consumption

Application and function

The new electro-thermal actuator TS+ is an evolution of the reliable and proven TS actuator. Clearly smaller in size, the TS+ enjoys the same technical attributes and the high quality standard of its predecessor.


The TS+ is robust and silent. The manual position makes installation and commissioning very easy. The valve position indicator displays the current status and stroke position.

The TS+ will initially be available in 230 V and 24 V versions, both are normally closed.

Technical data

Type	TS+ 5.11/230	TS+ 6.11/24
Product code	0493 1001 1015	0492 1001 1015
Supply voltage	230 V~ 50 Hz	24 V~
Switching current	< 1 A	< 0,5 A
Power consumption	2,5 W	
Thermal actuator	open / closed	
Valve type	normally closed	
Connecting cable	2 x 0.5 mm ² , 100 cm long (cable length can be modified on request) free core cable ends	
Protection type	IP 54	
Isolation	Class II	
Stroke	4,5 mm	
Available valve connections	M 30 x 1.5 mm	
Weight	approx. 120 g	
Dimensions	46 mm Ø, 80.4 mm height in open condition	
Storage temperature	-25...70°C	
Operating temperature	0...50°C	

Dimensions



EBERLE

EBERLE Controls GmbH

Klingenhofstraße 71

D-90411 Nürnberg

T +49(0)911 56 93 0

F +49(0)911 56 93 536

E-Mail: info.eberle@invensyscontrols.com

www.eberle.de